



# MAXQUICK®

## CEMENT BASE, WATERPROOF DECORATIVE COATING FOR INTERIOR OR EXTERIOR SURFACES AND SWIMMING POOLS

### DESCRIPTION

MAXQUICK is a waterproof decorative finish for exterior and interior surfaces. It is a cement base material ideal as a finish coat for cement mortars, concrete, prefabricated panels and brick.

### APPLICATIONS

As a final coat for swimming pools, to be applied straight over stucco or over MAXSEAL

### ADVANTAGES

- Low consumption.
- Decorative and waterproof at the same time.
- The product transpires; it does not create internal condensation.
- Lasts longer than ordinary paints.
- Available in six different colours.
- Washable - easily cleaned with water.
- Seals and fills pores in mortar, concrete and brick.

### HOW TO USE

**Preparation of the surface.** Clean the surface until it is free of all dirt, dust, grease, or any other foreign substance or loose particles. Seal all cracks and voids with MAXREST. Wet the surface to be coated and wait five to ten minutes before applying MAXQUICK.

**Preparation of the product.** In a clean container, put the amount of MAXQUICK you wish to mix. Add the water gradually while mixing. You can mix either manually, with a trowel or with a hand drill mixer, which will give greater uniformity and a faster mix.

Once the mix has a creamy consistency, let it rest for fifteen minutes. Then, mix again and begin the application immediately. Apply a uniform coat. Cover a little area at a time and try to coat these quickly. Do not touch up once time has elapsed. If necessary, apply a second coat when dry.

Do not apply MAXQUICK on surfaces that are too wet; wait until all surface water disappears.

Add approximately eight litres of water for every 25 kilograms of MAXQUICK. If the surface to which it is to be applied is very smooth, use MAXCRYL to prepare the MAXQUICK mix. Add three parts water to one part MAXCRYL and then use this liquid to prepare the MAXQUICK mix. This preparation may be increased, depending on the conditions of the surface to be treated.

**In warm weather.** Avoid using MAXQUICK under a bright sun. If you have no choice, we recommend using MAXCRYL and wetting the surface well before application. Later spray a fine mist of water to the surface to produce a better finish and cure.

**In cold weather conditions.** Wet the surface before applying MAXQUICK. Use MAXCRYL in the mix. Do not apply MAXQUICK at temperatures below 5° C, or if the temperature is expected to drop to such level within 24 hours of application.

**Working tools.** Use a fine hair brush or a fine artificial fibre brush, a foam roller or spray gun.

## SPECIFIC APPLICATION

**For swimming pools.** Two coats of MAXSEAL for waterproofing, and one coat of MAXQUICK for a smooth finish.

**For exterior walls and surfaces exposed to the weather.** That must be waterproofed and decorated. First coat of MAXSEAL with a brush and a second coat of MAXQUICK with a brush, roller or spray.

**For decorative uses as an exterior coating.** Two coats of MAXQUICK the first with a brush and the second with a brush, roller or spray gun.

## CONSUMPTION

0.2 – 0.5 kg./m2 per coat.

## COLOURS

White, Ivory, Cream, Green, Blue, Pearl Grey, Pink.

## PACKAGING

25 kilogram drums.

## CAUTION

As all cement products, MAXQUICK is abrasive and protective rubber must be used to prepare the mixture and apply it. If any of the mixture gets into the eyes, rinse thoroughly with clean water, but do not rub. If irritation continues, consult a doctor.

## GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. DRIZORO reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. Our guarantee covers exclusively the quality of the manufactured product. We shall not accept responsibility exceeding the value of the purchased product.



### **DRIZORO, S.A.**

C/ Primavera 50-52 Parque Industrial Las Monjas  
28850 TORREJON DE ARDOZ – MADRID (SPAIN)  
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13



e-mail: [info@drizoro.com](mailto:info@drizoro.com) Web site: [drizoro.com](http://drizoro.com)